



T

Multifunction Meters Transducers & Isolators Temperature Controllers Converters & Recorders Digital Panel Meters Current Transformers

Analogue Panel Meters

Shunts

**Digital Multimeters** 

**Clamp Meters** 

**Insulation Testers** 

# XMER 3PH SERIES

User Manual - Issue 1.0




#### Features

- → Compact size
- → Wide range of system current Ratings
- → Hinged terminal cover
- → Various mounting options like DIN rail mounting, Wall mounting
- → Terminal with self lifting screw with dual connection facility giving access from both sides of transformers


#### 1. General specification


| Applicable standard       | IEC/EN60044-1, IEC61869-1, BS3938, BS7626                                  |
|---------------------------|--|
| Case                      | 10% glass filled polycarbonate, flame retardant grades classified UL 94V-0 |
| Insulation class          | E(120°C max)   |
| Test voltage              | 3KV 50 Hz for 1 minute   |
| Operating frequency       | 50Hz   |
| Rated Primary current     | 40A to 800A  |
| Rated secondary current   | 5A standard  |
| Continuous current        | 1.2X Rated current   |
| Rated system voltage      | 0.72/3KV   |
| Ambient temperature range | -20 to +45°C   |
| Storage temperature range | -50 to +80°C   |

#### XMER 3PH 75-15(60)



| CT Ratio | Class 0.5 | Class 1 | Class 3 |
|----------|-----------|---------|---------|
| 60/5A    | -         | 1VA     | 2VA     |
| 100/5A   | -         | 1.5VA   | 2.5VA   |
| 125/5A   | -         | 1.5VA   | 2.5VA   |
| 150/5A   | 1.5VA     | 1.5VA   | 2.5VA   |
| 160/5A   | 1.5VA     | 1.5VA   | 2.5VA   |









# XMER 3PH 105-21(40)









| CT Ratio | Class 0.5 | Class 1 | Class 3 |
|----------|-----------|---------|---------|
| 100/5A   | -         | 1.5VA   | 2VA     |
| 125/5A   | -         | 1.5VA   | 2.5VA   |
| 150/5A   | -         | 1.5VA   | 2.5VA   |
| 160/5A   | 1.5VA     | 1.5VA   | 2.5VA   |
| 200/5A   | 1.5VA     | 1.5VA   | 2.5VA   |
| 250/5A   | 1.5VA     | 1.5VA   | 2.5VA   |



# XMER 3PH 140-31(40)






3

| CT Ratio | Class 0.5 | Class 1 | Class 3 |
|----------|-----------|---------|---------|
| 250/5A   | 1.5VA     | 1.5VA   | 2.5VA   |
| 300/5A   | 2.5VA     | 2.5VA   | 3.75VA  |
| 400/5A   | 2.5VA     | 2.5VA   | 3.75VA  |
| 500/5A   | 2.5VA     | 2.5VA   | 3.75VA  |
| 600/5A   | 2.5VA     | 2.5VA   | 3.75VA  |
| 630/5A   | 2.5VA     | 2.5VA   | 3.75VA  |



# XMER 3PH 185-27(45)






| CT Ratio | Class 1 | Class 3 |
|----------|---------|---------|
| 40/5A    | -       | 1.25VA  |
| 60/5A    | -       | 1.5VA   |
| 80/5A    | -       | 1.5VA   |
| 100/5A   | 1.5VA   | 1.5VA   |
| 150/5A   | 1.5VA   | 1.5VA   |
| 200/5A   | 2.5VA   | 2.5VA   |
| 250/5A   | 2.5VA   | 2.5VA   |
| 300/5A   | 5VA     | 5VA     |
| 400/5A   | 5VA     | 5VA     |
| 500/5A   | 5VA     | 5VA     |



# XMER 3PH 185-37(45)





| CT Ratio | Class 1 | Class 3 |
|----------|---------|---------|
| 300/5A   | 2.5VA   | 2.5VA   |
| 400/5A   | 5VA     | 5VA     |
| 500/5A   | 5VA     | 5VA     |
| 600/5A   | 5VA     | 5VA     |
| 800/5A   | 5VA     | 5VA     |



Contact



1 Warner Drive Springwood Industrial Estate Braintree, Essex CM7 2YW Tel: 01376 335271 E-mail: sales@sifamtinsley.com

www.sifamtinsley.co.uk